



Rodamiento de agujas NAF304517-IKO

NAF304517-IKO



Shell	Identification number	Mod. (ref.)	Boundary dimensions - mm					Standard mounting dimensions - mm				
mm		g	d	D	C	$r_{s max}$	r_w	d_b	D_s Max.	d_s Min.	d_s Max.	D_b
30	NAF 304517	101	30	46	17	0.3	35	39.5	43	32	34	35.6
	NAFW 304526	155	30	46	26	0.3	35	39.5	43	32	34	35.6
	NAF 304716	107	30	47	16	0.3	35	40.4	45	32	34	35.6
	NAFW 304732	215	30	47	32	0.3	35	40.4	45	32	34	35.6

Ball-type load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾	Assembled inner ring
N	N	rpm	
20 500	36 900	14 000	LRT 303517
26 600	51 500	14 000	LRT 303526
23 100	33 900	14 000	LRT 303516
39 500	67 800	14 000	LRT 303532



Rodamiento de agujas NAF304517-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	45
C - Espesor (mm)	17
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	NAF
Unidad de venta	pieza

