



Rodamiento de agujas NAF304716-IKO

NAF304716-IKO



Shell	Identification number	Mod. (Ref.)	Boundary dimensions - mm					Standard mounting dimensions - mm				
mm		g	d	D	C	$r_{s max}$ (°)	F_w	d_h	D_h Max.	d_h Min.	d_h Max.	D_h
30	NAF 304517	101	30	46	17	0.3	35	39.5	43	32	34	35.6
	NAFW 304526	155	30	46	26	0.3	35	39.5	43	32	34	35.6
	NAF 304716	107	30	47	16	0.3	35	40.4	45	32	34	35.6
	NAFW 304732	215	30	47	32	0.3	35	40.4	45	32	34	35.6

Ball-type	Basic static	Allowable	Assembled
load rating	load rating	rotational	inner ring
C	C_0	speed ⁽²⁾	
N	N	rpm	
20 500	36 900	14 000	LRT 303517
26 600	51 500	14 000	LRT 303526
23 100	33 900	14 000	LRT 303516
39 500	67 800	14 000	LRT 303532



Rodamiento de agujas NAF304716-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	47
C - Espesor (mm)	16
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	NAF
Unidad de venta	pieza

