



Rodamiento de agujas NAF405517-IKO

NAF405517-IKO



Shell	Identification number	Mass (ref.)	Boundary dimensions - mm					Standard mounting dimensions - mm				
mm		g	d	D	C	$r_{s\max}$	F_w	d_h	D_h Max.	d_h Min.	d_h Max.	D_h
40	NAF 405517	123	40	55	17	0.3	45	48.5	53	42	44	45.8
	NAFW 405534	255	40	55	34	0.3	45	48.5	53	42	44	45.8
	NAF 406220	235	40	62	20	0.3	45	50.9	60	42	44	45.8
	NAFW 406240	475	40	62	40	0.3	45	50.9	60	42	44	45.8

Ball-bearing load rating C	Basic static load rating C_0	Allowable rotational speed ⁽¹⁾	Assembled inner ring
N	N	rpm	
23 300	47 100	11 000	LRT 404517
39 900	94 200	11 000	LRT 404534
33 200	53 300	11 000	LRT 404520
56 900	107 000	11 000	LRT 404540



Rodamiento de agujas NAF405517-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	40
D - Diámetro exterior (mm)	55
C - Espesor (mm)	17
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	NAF
Unidad de venta	pieza

