



Rodamiento de agujas NAF457220-IKO

NAF457220-IKO



Shell	Identification number	Mass (ref.)	Boundary dimensions - mm					Standard mounting dimensions - mm				
mm		g	d	D	C	r_{smax} (°)	F_w	d_b	D_b Max.	d_b Min.	d_b Max.	D_b
45	NAF 456220	195	45	62	20	0.3	50	54.2	60	47	49	50.8
	NAFW 456240	390	45	62	40	0.3	50	54.2	60	47	49	50.8
	NAF 457220	340	45	72	20	1	55	60.9	67	50	54	55.8
	NAFW 457240	685	45	72	40	1	55	60.9	67	50	54	55.8

Ball-bearing load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾	Assembled inner ring
N	N	rpm	
27 100	59 300	10 000	LRT 455020
46 400	119 000	10 000	LRT 455040
37 400	66 400	9 000	LRT 455520
64 100	133 000	9 000	LRT 455540



Rodamiento de agujas NAF457220-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	45
D - Diámetro exterior (mm)	72
C - Espesor (mm)	20
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	NAF
Unidad de venta	pieza

