


Rodillo de apoyo NATR10-SKF

NATR10-SKF



Dimensions							Mass	Designation
D	d	C	B	d ₂	F	F _{1,2}		
mm							kg	—
30	10	14	15	23	0,6	—	0,064	NATR 10
	10	14	15	23	0,6	—	0,064	NATR 10 PPA
	10	14	15	23	0,6	—	0,065	NATV 10
	10	14	15	23	0,6	—	0,065	NATV 10 PPA

Designation	Basic load ratings		Fatigue load limit	Maximum radial forces		Limiting speed
	C	C ₀	P ₀	dynamic F _r	static F ₀	
—	kN		kN	kN	kN	rpm
NATR 10	6,64	8	0,88	7,8	11,2	4 800
NATR 10 PPA	6,64	8	0,88	7,8	11,2	4 800
NATV 10	8,97	14,6	1,66	11	15,6	3 200
NATV 10 PPA	8,97	14,6	1,66	11	15,6	3 200



Rodillo de apoyo NATR10-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	10
D - Diámetro exterior (mm)	30
C - Espesor (mm)	15
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula exterior abombada
Rodamiento serie	NATR
Unidad de venta	pieza

