

# Rodillo de apoyo NATR10-X-SKF

## NATR10-X-SKF

**LE BON  
ROULEMENT**

NATR

NATR - PPA

NATV

NATV - PPA

| Dimensions |    |    |    |                |                  |                        | Mass  | Designation |
|------------|----|----|----|----------------|------------------|------------------------|-------|-------------|
| D          | d  | C  | B  | d <sub>2</sub> | F <sub>min</sub> | F <sub>1,2</sub><br>mm |       |             |
| mm         |    |    |    |                |                  |                        | kg    | —           |
| 30         | 10 | 14 | 15 | 23             | 0,6              | —                      | 0,064 | NATR 10     |
|            | 10 | 14 | 15 | 23             | 0,6              | —                      | 0,064 | NATR 10 PPA |
|            | 10 | 14 | 15 | 23             | 0,6              | —                      | 0,065 | NATV 10     |
|            | 10 | 14 | 15 | 23             | 0,6              | —                      | 0,065 | NATV 10 PPA |

| Designation | Basic load ratings |                          | Fatigue<br>load limit<br>P <sub>0</sub> | Maximum<br>radial forces  |                          | Limiting<br>speed<br>n/min |
|-------------|--------------------|--------------------------|-----------------------------------------|---------------------------|--------------------------|----------------------------|
|             | dynamic<br>C       | static<br>C <sub>0</sub> |                                         | dynamic<br>F <sub>r</sub> | static<br>F <sub>0</sub> |                            |
| —           | kN                 |                          | kN                                      | kN                        |                          |                            |
| NATR 10     | 6,64               | 8                        | 0,88                                    | 7,8                       | 11,2                     | 4 800                      |
| NATR 10 PPA | 6,64               | 8                        | 0,88                                    | 7,8                       | 11,2                     | 4 800                      |
| NATV 10     | 8,97               | 14,6                     | 1,66                                    | 11                        | 15,6                     | 3 200                      |
| NATV 10 PPA | 8,97               | 14,6                     | 1,66                                    | 11                        | 15,6                     | 3 200                      |



**Rodillo de apoyo NATR10-X-SKF**

| Caractéristique            | Valeur                     |
|----------------------------|----------------------------|
| d - Diámetro interior (mm) | 10                         |
| D - Diámetro exterior (mm) | 30                         |
| C - Espesor (mm)           | 15                         |
| Marca                      | SKF                        |
| Tipo del rodamiento        | Rodillo de apoyo de agujas |
| Tipo de sellado            | No estanco                 |
| Tipo de jaula              | Acero                      |
| Especificaciones           | Jaula exterior plana       |
| Rodamiento serie           | NATR                       |
| Unidad de venta            | pieza                      |

