


Rodillo de apoyo NATR17-SKF

NATR17-SKF

LE BON ROULEMENT



Dimensions							Mass	Designation
D	d	C	B	d ₁	F	F _{1,2}		
mm							kg	-
40	17	20	21	32	3	-	0,14	NATR 17
	17	20	21	32	3	-	0,14	NATR 17 PPA
	17	20	21	32	3	-	0,15	NATV 17
	17	20	21	32	3	-	0,15	NATV 17 PPA

Designation	Basic load ratings		Fatigue load limit	Maximum radial forces		Limiting speed
	dynamic	static		dynamic	static	
-	C	C ₀	P ₀	F _r	F _{0r}	r/min
NATR 17	30,5	14,6	1,73	12,5	18	3 400
NATR 17 PPA	30,5	14,6	1,73	12,5	18	3 400
NATV 17	14,2	24,5	3,1	17	24,5	2 200
NATV 17 PPA	14,2	24,5	3,1	17	24,5	2 200



Rodillo de apoyo NATR17-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	17
D - Diámetro exterior (mm)	40
C - Espesor (mm)	21
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula exterior abombada
Rodamiento serie	NATR
Unidad de venta	pieza

