



Rodillo de apoyo NATR20-SKF

NATR20-SKF



LE BON
ROULEMENT



NATR

NATR - PPA

NATV

NATV - PPA

Dimensions						Mass		Designation
D	d	C	B	d ₂	F	F _{1,2}		
mm						mm	kg	—
47	20	24	25	37	1	—	0,25	NATR 20
	20	24	25	37	1	—	0,25	NATR 20 PPA
	20	24	25	37	1	—	0,25	NATV 20
	20	24	25	37	1	—	0,25	NATV 20 PPA

Designation	Basic load ratings		Fatigue	Maximum		Limiting
	C	C ₀	load limit	radial forces	static	
—	kN		kN	kN	kN	rpm
NATR 20	34,7	24,5	2,9	23,6	33,5	3 000
NATR 20 PPA	34,7	24,5	2,9	23,6	33,5	3 000
NATV 20	39,4	43,5	5	30,5	43	1 900
NATV 20 PPA	39,4	43,5	5	30,5	43	1 900



Rodillo de apoyo NATR20-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	20
D - Diámetro exterior (mm)	47
C - Espesor (mm)	25
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula exterior abombada
Rodamiento serie	NATR
Unidad de venta	pieza

