


Rodillo de apoyo NATR25-X-PP-A-SKF

NATR25-X-PPA-SKF

LE BON ROULEMENT



NATR NATR - PP NATV NATV - PP

Dimensions							Mass	Designation
D	d	C	B	d ₁	F	F _{1.2}		
mm							kg	—
S2	25	24	25	42	3	—	0,28	NATR 25
	25	24	25	42	3	—	0,28	NATR 25 PPA
	25	24	25	42	1	—	0,29	NATV 25
	25	24	25	42	1	—	0,29	NATV 25 PPA

Designation	Basic load ratings		Fatigue load limit	Maximum radial forces		Limiting speed
	C	C ₀		P _r	F _r	
—	kN		kN	kN	kN	r/min
NATR 25	34,7	25,5	3,3	21,6	31	2 400
NATR 25 PPA	34,7	25,5	3,3	21,6	31	2 400
NATV 25	19,8	44	6,1	28,5	40,5	1 600
NATV 25 PPA	19,8	44	5,3	28,5	40,5	1 600



Rodillo de apoyo NATR25-X-PP-A-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	25
D - Diámetro exterior (mm)	52
C - Espesor (mm)	25
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de agujas
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Tipo de jaula	Acero
Especificaciones	Jaula exterior plana
Rodamiento serie	NATR
Unidad de venta	pieza

