


Rodillo de apoyo NATR35-X-PP-A-SKF

NATR35-X-PPA-SKF

LE BON
ROULEMENT



NATR

NATR - PPM

NATV

NATV - PPM

Dimensions							Mass	Designation
D	d	C	B	d ₁	F _{min}	F _{1,2}		
mm					mm	mm	kg	—
72	35	28	29	58	1.1	—	0.64	NATR 35 PPA
	35	28	29	58	1.1	—	0.65	NATV 35 PPA

Designation	Basic load ratings		Fatigue load limit	Maximum radial forces		Limiting speed
	C	C ₀	P ₀	F _r	F ₀	
—	kN		kN	kN	kN	rpm
NATR 35 PPA	24.6	43	5.3	33.5	48	1 600
NATV 35 PPA	31.9	72	8.8	43	62	1 100



Rodillo de apoyo NATR35-X-PP-A-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	35
D - Diámetro exterior (mm)	72
C - Espesor (mm)	29
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de agujas
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Tipo de jaula	Acero
Especificaciones	Jaula exterior plana
Rodamiento serie	NATR
Unidad de venta	pieza

