


Rodillo de apoyo NATV5-SKF

NATV5-SKF



NATR



NATR-PPH



NATV



NATV-PPH

Dimensions							Mass	Designation
D	d	C	B	d ₂	F _{min}	F _{1,2}		
mm					mm	mm	kg	—
S6	5	11	12	12	0,15	—	0,014	NATR S
	5	11	12	12	0,15	—	0,014	NATR S PPH
	5	11	12	12	0,15	—	0,015	NATV S
	5	11	12	12	0,15	—	0,015	NATV S PPH

Designation	Basic load ratings		Fatigue load limit	Maximum radial forces		Limiting speed
	C	C ₀		P _r	F ₀	
—	kN		kN	kN	kN	rpm
NATR S	3,14	3,2	0,345	2,9	4,15	6 000
NATR S PPH	3,14	3,2	0,345	2,9	4,15	6 000
NATV S	4,73	4,55	0,72	4,05	5,7	4 300
NATV S PPH	4,73	4,55	0,72	4,05	5,7	4 300



Rodillo de apoyo NATV5-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	5
D - Diámetro exterior (mm)	16
C - Espesor (mm)	12
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula exterior abombada
Rodamiento serie	NATV
Unidad de venta	pieza

