


Rodillo de apoyo NATV6-X-PP-A-SKF

NATV6-X-PPA-SKF



LE BON
ROULEMENT



NATR



NATR - PPA



NATV



NATV - PPA

Dimensions							Mass	Designation
D	d	C	B	d ₂	F _{min}	F _{1,2} mm	kg	—
mm								
19	6	11	12	14	0.15	—	0.02	NATR 6
	6	11	12	14	0.15	—	0.02	NATR 6 PPA
	6	11	12	14	0.15	—	0.021	NATV 6
	6	11	12	14	0.15	—	0.021	NATV 6 PPA

Designation	Basic load ratings		Fatigue load limit P ₀	Maximum radial forces		Limiting speed
	C	C ₀		dynamic F _r	static F ₀	
—	kN		kN	kN	kN	r/min
NATR 6	3.47	3.8	0.415	3.8	5.5	5 600
NATR 6 PPA	3.47	3.8	0.415	3.8	5.5	5 600
NATV 6	5.28	8	0.88	5.3	7.35	4 000
NATV 6 PPA	5.28	8	0.88	5.3	7.35	4 000



Rodillo de apoyo NATV6-X-PP-A-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	6
D - Diámetro exterior (mm)	19
C - Espesor (mm)	12
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de agujas
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Tipo de jaula	Acero
Especificaciones	Jaula exterior plana
Rodamiento serie	NATV
Unidad de venta	pieza

