



Rodillo de apoyo NATV15-SKF

NATV15-SKF




LE BON
ROULEMENT



NATR NATR - PPM NATV NATV - PPM

Dimensions							Mass	Designation
D	d	C	B	d ₂	F _{min}	F _{1,2}		
mm							kg	—
35	15	18	19	27	0.6	—	0.1	NATR 15
	15	18	19	27	0.6	—	0.1	NATR 15 PPM
	15	18	19	27	0.6	—	0.11	NATV 15
	15	18	19	27	0.6	—	0.11	NATV 15 PPM

Designation	Basic load ratings		Fatigue load limit	Maximum radial forces		Limiting speed
	C	C ₀	P ₀	F _r dynamic	F _r static	
—	kN		kN	kN	kN	rpm
NATR 15	9.52	11.7	1.56	11.4	16.3	4 000
NATR 15 PPM	9.52	11.7	1.56	11.4	16.3	4 000
NATV 15	12.3	23.2	2.7	14.6	20.8	2 600
NATV 15 PPM	12.3	23.2	2.7	14.6	20.8	2 600



Rodillo de apoyo NATV15-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	15
D - Diámetro exterior (mm)	35
C - Espesor (mm)	19
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula exterior abombada
Rodamiento serie	NATV
Unidad de venta	pieza

