



Rodillo de apoyo NATV17-SKF

NATV17-SKF



LE BON
ROULEMENT



NATR NATR - PPM NATV NATV - PPM

Dimensions							Mass	Designation
D	d	C	B	d ₂	F	F _{1,2}		
mm							kg	—
40	17	20	21	32	5	—	0,14	NATR 17
	17	20	21	32	5	—	0,14	NATR 17 PPM
	17	20	21	32	5	—	0,15	NATV 17
	17	20	21	32	5	—	0,15	NATV 17 PPM

Designation	Basic load ratings		Fatigue load limit	Maximum radial forces		Limiting speed
	C	C ₀	P ₀	dynamic F _r	static F ₀	
—	kN		kN	kN	kN	rpm
NATR 17	30,5	14,6	1,73	12,5	18	3 400
NATR 17 PPM	30,5	14,6	1,73	12,5	18	3 400
NATV 17	14,2	24,5	3,1	17	24,5	2 200
NATV 17 PPM	14,2	24,5	3,1	17	24,5	2 200



Rodillo de apoyo NATV17-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	17
D - Diámetro exterior (mm)	40
C - Espesor (mm)	21
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula exterior abombada
Rodamiento serie	NATV
Unidad de venta	pieza

