


Rodillo de apoyo NATV17-X-PP-A-SKF

NATV17-X-PPA-SKF

 **LE BON
ROULEMENT**



Dimensions							Mass	Designation
D	d	C	B	d ₂	F _{min}	F _{1,2} mm	kg	—
<i>mm</i>								
40	17	20	21	32	5	—	0,14	NATR 17
	17	20	21	32	5	—	0,14	NATR 17 PPA
	17	20	21	32	5	—	0,15	NATV 17
	17	20	21	32	5	—	0,15	NATV 17 PPA

Designation	Basic load ratings		Fatigue load limit P ₀	Maximum radial forces		Limiting speed
	C	C ₀		F _r	F ₀	
—	kN		kN	kN		rpm
NATR 17	30,5	14,6	1,73	12,5	18	3 400
NATR 17 PPA	30,5	14,6	1,73	12,5	18	3 400
NATV 17	14,2	24,5	3,1	17	24,5	2 200
NATV 17 PPA	14,2	24,5	3,1	17	24,5	2 200



Rodillo de apoyo NATV17-X-PP-A-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	17
D - Diámetro exterior (mm)	40
C - Espesor (mm)	21
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de agujas
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Tipo de jaula	Acero
Especificaciones	Jaula exterior plana
Rodamiento serie	NATV
Unidad de venta	pieza

