


Rodillo de apoyo NATV30-SKF

NATV30-SKF

LE BON
ROULEMENT



Dimensions							Mass	Designation
D	d	C	B	d ₂	F _{min}	F _{1,2} mm	kg	—
mm								
62	30	28	29	51	1	—	0.47	NATR 30
	30	28	29	51	1	—	0.47	NATR 30 PPM
	30	28	29	51	1	—	0.48	NATV 30
	30	28	29	51	1	—	0.48	NATV 30 PPM

Designation	Basic load ratings		Fatigue	Maximum		Limiting
	C	C ₀	load limit	radial forces	static	
—	kN		kN	kN	kN	r/min
NATR 30	22.9	37.5	4.55	26.5	38	1 800
NATR 30 PPM	22.9	37.5	4.55	26.5	38	1 800
NATV 30	25.2	62	7.65	34.5	49	1 400
NATV 30 PPM	29.2	62	7.65	34.5	49	1 400



Rodillo de apoyo NATV30-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	62
C - Espesor (mm)	29
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula exterior abombada
Rodamiento serie	NATV
Unidad de venta	pieza

