

# Rodamiento de agujas NK1A5906-A-NTN

NK1A5906-A-NTN

**LE BON ROULEMENT**

Basic dimensions				Basic load ratings								Limiting dimensions		
mm	in	r	r	dynamic		static		dynamic		static		mm	in	
				C <sub>10</sub>	C <sub>90</sub>	C <sub>10</sub>	C <sub>90</sub>	C <sub>10</sub>	C <sub>90</sub>	C <sub>10</sub>	C <sub>90</sub>			
30	47	23	35	0.3	19 400	33 500	1 980	3 100	5 400	8 580	550	870	7 900	11 000

  

Bearing numbers	Bearing dimensions				Mass kg
	d <sub>1</sub>	D <sub>1</sub>	D <sub>2</sub>	r <sub>1</sub>	
NKGA 5906	32.5	30	44.5	0.3	0.147



**Rodamiento de agujas NK1A5906-A-NTN**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	47
C - Espesor (mm)	23
Marca	NTN
Tipo del rodamiento	De agujas combinadas
Tipo de sellado	No estanco
Rodamiento serie	NKIA
Unidad de venta	pieza

