


Rodillo de apoyo NUTR1747-X

NUTR1747-X





NUTR

Diamètre extérieur (mm)	Diamètre intérieur (mm)	Style Designation	Poids (g) Weight (g)	Dimensions (mm) Dimensions (inch)					Coefficients de charge N Bearing Load Rating N				Vitesse de rotation N ₁ (rpm)
				d	B	C	d ₁	D	Dynamique C _d	Statique C ₀	Dynamique C _d	Statique C ₀	
47		NUTR 17 47	220	17	47	21	20	22	28 000	28 000	21 300	28 000	5 500
		PWTR 17 47.2R5	220	17	47	21	20	22	16 400	16 400	14 800	16 400	5 000
		NUTR 20 47	245	20	47	25	24	27	16 400	33 000	28 000	35 000	4 200
		PWTR 20.2R5	245	20	47	25	24	27	18 300	25 500	23 200	25 500	3 800



Rodillo de apoyo NUTR1747-X

Caractéristique	Valeur
d - Diámetro interior (mm)	17
D - Diámetro exterior (mm)	47
C - Espesor (mm)	21
Marca	Genérica alta calidad
Tipo del rodamiento	Rodillo de apoyo de rodillo
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula exterior plana
Rodamiento serie	NUTR
Unidad de venta	pieza

