

Rodamiento de agujas NA22/8-2RS

NA22/8-2RS





NA 22_2RS



NA 22_2RS

États et variantes (mm) Outside Diameter (mm)	Type Designation				Dimensions (mm) Dimensions (mm)							Coefficients de charge R Basis Load Rating R				Vitesse limite (1000 rpm)
	Sans bagues individueles without rings	Poids (g) Weight (g)	Avec bagues individuelles with rings	Poids (g) Weight (g)	D	d	F F _u	B	C	d ₁	D ₁	Bore D ₁ (mm)	Bore D ₁ (mm)	Bore D ₁ (mm)	Bore D ₁ (mm)	
24	NA 22/8 2RS	28	NA 22/8 2RS	34	34	8	12	12	11.8	18	5.490	5.200	4.000	4.000	14.000	



Rodamiento de agujas NA22/8-2RS

Caractéristique	Valeur
d - Diámetro interior (mm)	8
D - Diámetro exterior (mm)	24
C - Espesor (mm)	12
Marca	Genérica alta calidad
Tipo del rodamiento	De agujas
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Tipo de jaula	Acero
Especificaciones	Jaula exterior abombada
Rodamiento serie	NA
Unidad de venta	pieza

