

Rodamiento de agujas NA2207-2RS

NA2207-2RS





NA 22_2RS



NA 22_2RS

Éléments extérie- rieur (mm) Outside Dimension (mm)	Sigle Designation				Dimensions (mm) Dimensions (mm)							Coefficients de charge R Basis Load Rating R				Vitesse limite (1000rpm)
	Sans bagues indivisible Without R	Poids (g) Weight (g)	Avec bagues indivisible With R	Poids (g) Weight (g)	D	d	F Fw	B	C	d1	Dimensions (mm)	Statique St C	Dynamic St C	Dynamic St C	Dynamic St C	
72	RNA 2207 2RS	432	NA 2207 2RS	300	72	65	42	28	22.7	90	28.580	44.200	22.000	33.700	2.200	



Rodamiento de agujas NA2207-2RS

Caractéristique	Valeur
d - Diámetro interior (mm)	35
D - Diámetro exterior (mm)	72
C - Espesor (mm)	23
Marca	Genérica alta calidad
Tipo del rodamiento	De agujas
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Tipo de jaula	Acero
Especificaciones	Jaula exterior abombada
Rodamiento serie	NA
Unidad de venta	pieza

