



Rodamiento de agujas NA2206-LL-3AS-NTN

NA2206-LL-3AS-NTN





Type NA22-LL
(With inner ring)



Type RNA22-LL
(Without inner ring)

Boundary dimensions										Basic load ratings				Load ratings of truck	
D	B	C	d	e	f	r	R	P	n max	dynamic N	static N	dynamic kgf	static kgf	N	kgf
62	20	19.8	30	35	10.041 +0.029	43	35	0.3		21 400	34 500	2 190	3 500	6 950	22 200

Limiting speeds rpm	Bearing numbers		Mass (approx.) kg	
	Type	Type	Type	Type
	NA22-LL	RNA22-LL	NA22-LL	RNA22-LL
4 300	NA2206LL	RNA2206LL	0.322	0.284



Rodamiento de agujas NA2206-LL-3AS-NTN

Caractéristique	Valeur
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	62
C - Espesor (mm)	20
Marca	NTN
Tipo del rodamiento	De agujas
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Tipo de jaula	Acero
Especificaciones	Jaula exterior abombada
Rodamiento serie	NA
Unidad de venta	pieza

