

Rodamiento de agujas NAST12-IKO

NAST12-IKO

**LE BON
ROULEMENT**

NAST...R

NAST

NAST...ZZR

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm							Basic dynamic load rating C N	Basic static load rating C ₀ N	Assembled inner ring
	Open type			d	D	B	C	r _s max	r _{fs} max	F _W			
	Crowned outer ring	Cylindrical outer ring											
12	NAST 12 R	NAST 12	58	12	32	12	11.8	1	0.3	16	10 500	10 900	LRT 121612 S

Shaft dia. mm	Identification number				Mass (Ref.) g
	Shield type		Sealed type		
	Crowned outer ring	Cylindrical outer ring	Crowned outer ring	Cylindrical outer ring	
12	NAST 12 ZZR	NAST 12 ZZ	NAST 12 ZZUUR	NAST 12 ZZUU	75



Rodamiento de agujas NAST12-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	12
D - Diámetro exterior (mm)	32
C - Espesor (mm)	12
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula exterior plana
Rodamiento serie	NAST
Unidad de venta	pieza

