

Rodamiento de agujas NAST8-IKO

NAST8-ZZ-IKO


**LE BON
ROULEMENT**

NAST...R

NAST

NAST...ZZR

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm								Basic dynamic load rating C N	Basic static load rating C ₀ N	Assembled inner ring
	Open type			d	D	B	C	r ₁ max	r ₂ max	r ₃ max	r ₄ max			
8	NAST 8 R	NAST 8	28	8	24	10	9.8	0.6	0.3	12		5 650	5 890	LRT 81210 S

Shaft dia. mm	Identification number				Mass (Ref.) g
	Shield type		Sealed type		
8	Crowned outer ring	Cylindrical outer ring	Crowned outer ring	Cylindrical outer ring	39
	NAST 8 ZZR	NAST 8 ZZ	NAST 8 ZZUUR	NAST 8 ZZUU	



Rodamiento de agujas NAST8-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	8
D - Diámetro exterior (mm)	24
C - Espesor (mm)	10
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	Doble estanco metal (ZZ, 2Z, 2RZ)
Tipo de jaula	Acero
Especificaciones	Jaula exterior plana
Rodamiento serie	NAST
Unidad de venta	pieza

