

Rodamiento de agujas NKX12-Z

NKX12-Z

LE BON ROULEMENT

The technical drawing shows three views of the NKX12-Z needle roller bearing. On the left is an isometric view of the bearing. In the center are two cross-sectional views: the top one is labeled 'NKX' and the bottom one is labeled 'NKX-Z'. Both show the needle rollers (G) between the inner and outer rings, with dimensions for outer diameter (D), inner diameter (d), width (B), and roller diameter (D_r). The 'NKX-Z' view also shows the axial clearance (Z). On the right is a detail of the mounting dimensions, showing the bearing's position on a shaft with dimensions for bore diameter (D), shaft diameter (d), and axial clearance (Z).

Diamètre interne Bore diameter (mm)	Signe Designation		Dimensions (mm) Dimensions (mm)							Coefficients de charge (N) Load rating (N)				Masse linéaire Linear weight (mm)			
	Sans cage Without cage	Avec cage With cage	F _o	D	D _i	C	C ₁	C ₂	d _h	Radial / D _r / D _r	Radial / D _r / D _r	Radial / D _r / D _r	Radial / D _r / D _r	M ₀ (kg)	M ₁ (kg)		
12	NKX 12	NKX 12 Z	40	12	21	28.1	17.2	25	9	6.5	12	8 900	10 500	19 600	15 800	11 600	25.7



Rodamiento de agujas NKX12-Z

Caractéristique	Valeur
d - Diámetro interior (mm)	12
D - Diámetro exterior (mm)	21
C - Espesor (mm)	23
Marca	Genérica alta calidad
Tipo del rodamiento	De agujas combinadas
Tipo de jaula	Acero
Especificaciones	Lubricación con grasa
Rodamiento serie	NKX
Unidad de venta	pieza

