

# Rodamiento de agujas NKX10-T2-Z-NTN

NKX10-T2-Z-NTN

**LE BON ROULEMENT**

Type NKX-Z  
(With cover)

Dimensions											Basic load ratings			
$d_1$	$d$	$D_1$	$D$	$D_2$	$L$	$C_1$	$C_2$	$e$	$r_1$	$r_2$	Dynamic N	Static kN	Dynamic kg	Static kg
10	10	19	24	25	23	9	8.5	19.7	0.3		5 450	6 450	555	890

dynamic N	Basic load ratings		Limiting dimensions mm	Bearing numbers		Abutment diameters mm	Mass (approx.) kg
	static	dynamic		Type NKX	Type NKX-Z		
10 000	14 000	1 020	6 700	9 500	NKX10T2 NKX10T2Z	10 0.3	0.037 0.039



**Rodamiento de agujas NKX10-T2-Z-NTN**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	10
D - Diámetro exterior (mm)	19
C - Espesor (mm)	23
Marca	NTN
Tipo del rodamiento	De agujas combinadas
Tipo de jaula	Poliamido
Especificaciones	Lubricación con grasa
Rodamiento serie	NKX
Unidad de venta	pieza

