

Rodamiento de agujas NKX20-T2-NTN

NKX20-T2-NTN

LE BON ROULEMENT

Type NKX (Open type)

Dimensions											Basic load ratings			
d	D	C	C_1	C_2	r	y	ϕD_1	ϕD_2	ϕd	ϕd_1	Dynamic N	Static N _{st}	Dynamic N	Static N _{st}
20	30	36	10	10	0.5	30.7	19.5	10.5	30.7	0.5	16 400	27 100	1 070	2 780

dynamic N	Basic load ratings static		Limiting dimensions mm	Bearing numbers		Abutment dimensions mm		Mass (approx.) kg			
	static	dynamic		Type NKX	Type NKX-T2	d_1 min	d_2 max	Type NKX	Type NKX-T2		
14 200	24 700	1 450	2 520	5 200	7 500	NKX20T2	NKX20T2Z	29	0.5	0.085	0.090



Rodamiento de agujas NKX20-T2-NTN

Caractéristique	Valeur
d - Diámetro interior (mm)	20
D - Diámetro exterior (mm)	30
C - Espesor (mm)	30
Marca	NTN
Tipo del rodamiento	De agujas combinadas
Tipo de jaula	Poliamido
Especificaciones	Lubricación con aceite
Rodamiento serie	NKX
Unidad de venta	pieza

