

Rodamiento de agujas NKX25-NTN

NKX25-NTN

LE BON ROULEMENT

Type NKX (Open type)

Dimensions											Basic load ratings			
d	D	B	C	C_1	C_2	r	y	ϕF	ϕd	ϕD_1	Dynamic	Static	Dynamic	Static
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	N	kg	N	kg
25	42	37	42	30	11	0.6	9.5	37.7	0.6	14 200	24 000	1 400	2 430	

dynamic	Basic load ratings				Limiting dimensions		Bearing numbers		Abutment dimensions		Mass	
	dynamic	static	dynamic	static	gross	oil	Type	Type	d_1	d_2	Type	Type
N	C_{10}	C_{20}	C_{10}	C_{20}	mm	mm	NKX	NKX-2	min	max	AKX	NKX-2
19 600	37 000	1 990	3 900	4 600	6 500		NKX25T2	NKX25T2Z	35	0.6	0.125	0.132



Rodamiento de agujas NKX25-NTN

Caractéristique	Valeur
d - Diámetro interior (mm)	25
D - Diámetro exterior (mm)	42
C - Espesor (mm)	30
Marca	NTN
Tipo del rodamiento	De agujas combinadas
Tipo de jaula	Acero
Especificaciones	Lubricación con aceite
Rodamiento serie	NKX
Unidad de venta	pieza

