

Rodamiento de agujas NKX50-Z-NTN

NKX50-Z-NTN

LE BON ROULEMENT

Type NKX-Z
(With cover)

Dimensions											Basic load ratings			
d_1	d	D_1	D	D_2	L	C_1	C_2	α	r_{max}		Dynamic	static	Dynamic	static
mm	mm	mm	mm	mm	mm	N	N	°	mm		C_{10}	C_{010}	C_{10}	C_{010}
50	60	68.625	82	70	71.5	35	14	10	0.5		27 900	62 000	2 850	6 300

dynamic	Basic load ratings		static	Limiting dimensions	Bearing numbers		Abutment dimensions	Mass	
	static	dynamic			Type	Type		mm	kg
C_{10}	C_{010}	C_{10}	C_{010}	gross	oil	NKX	NKX-Z	d_1	d
28 800	75 500	2 850	7 200	3 100	4 500	NKX50	NKX50Z	62	66



Rodamiento de agujas NKX50-Z-NTN

Caractéristique	Valeur
d - Diámetro interior (mm)	50
D - Diámetro exterior (mm)	62
C - Espesor (mm)	35
Marca	NTN
Tipo del rodamiento	De agujas combinadas
Tipo de jaula	Acero
Especificaciones	Lubricación con grasa
Rodamiento serie	NKX
Unidad de venta	pieza

