

Rodamiento de agujas NKXR50-T2-Z-NTN

NKXR50-T2-Z-NTN

LE BON ROULEMENT

Type NKXR · Z (With cover)

Primary dimensions										Basic load ratings			
d	D	D_2	d_2	r_1	r_2	r_3	r_4	r_5	r_6	Dynamic	Static	Dynamic	Static
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	N	kN	kN	kN
50	60	60	71.5	35	14	10	65.5	0.8		27 900	62 000	2 850	6 300

Basic load ratings				Limiting dimensions		Bearing numbers		Mounting dimensions		Mass	
Dynamic	Static	Dynamic	Static	gross	of	Type NKXR	Type NKXR · Z	d_1	r_1	Type NKXR	Type NKXR · Z
N	kN	kN	kN	mm	mm			mm	mm	kg	kg
46 000	150 000	4 900	15 300	1 000	4 000	NKXR50T2	NKXR50T2Z	60	0.8	0.306	0.329



Rodamiento de agujas NKXR50-T2-Z-NTN

Caractéristique	Valeur
d - Diámetro interior (mm)	50
D - Diámetro exterior (mm)	62
C - Espesor (mm)	35
Marca	NTN
Tipo del rodamiento	De agujas combinadas
Tipo de jaula	Poliamido
Especificaciones	Lubricación con grasa
Rodamiento serie	NKXR
Unidad de venta	pieza

