

# Rodamiento de agujas NAX7040-Z-IKO

## NAX7040-Z-IKO

**LE BON ROULEMENT**

Shaft dia. mm	Identification number							
	Max (Ref.)	With dust cover	Max (Ref.)		Max (Ref.)	With dust cover	Max (Ref.)	
70	NAX 7040	555	NAX 7040Z	608	—	—	—	—

  

Boundary dimensions mm								Determination range d <sub>wa</sub> Min. mm	Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed rpm	
F <sub>sw</sub>	D	D <sub>1</sub>	D <sub>2</sub>	L	H	i <sub>1</sub>	r <sub>1, max</sub>		d <sub>1</sub>	Radial	Axial	Radial		Axial
70	85	95	96.5	40	18	11	1	70	85	55 500	43 100	120 000	101 000	3 500



**Rodamiento de agujas NAX7040-Z-IKO**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	70
D - Diámetro exterior (mm)	85
C - Espesor (mm)	40
Marca	IKO
Tipo del rodamiento	De agujas combinadas
Tipo de jaula	Acero
Especificaciones	Lubricación con grasa
Rodamiento serie	NAX
Unidad de venta	pieza

