

Rodamiento de agujas NAXI923-IKO

NAXI923-IKO

LE BON ROULEMENT

Shaft dia. mm	Identification number						d	D	D ₁	
	Mass (Ref.) g	With dust cover	Mass (Ref.) g		Mass (Ref.) g	With dust cover				Mass (Ref.) g
9	NAXI 923	49.5	NAXI 923Z	51.5	—	—	—	9	21	26

Boundary dimensions mm										Intermediate diameters mm		Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed rpm	Assembled inner ring
D ₂	L	B	H	l ₁	r _{max}	r _{min}	F _w	d ₁	d ₂	Min.	Max.	Radial	Axial	Radial	Axial		
27	23	16	9	6.5	0.3	0.3	12	12	20	11	11	9 250	9 670	11 200	11 100	9 000	LRT 91216



Rodamiento de agujas NAXI923-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	9
D - Diámetro exterior (mm)	21
C - Espesor (mm)	23
Marca	IKO
Tipo del rodamiento	De agujas combinadas
Tipo de jaula	Acero
Especificaciones	Lubricación con aceite
Rodamiento serie	NAXI
Unidad de venta	pieza

