

# Rodamiento axial de rodillos cónicos 29417-E-NSK

## 29417-E-NSK

**LE BON ROULEMENT**

Version E      Version Standard

Dimensions (mm)				Capacité de Charge				N <sub>201</sub>		Viscos (cSt) @ 30°C	Tolérance (Roulement)
d	D	T	r	C <sub>10</sub>	C <sub>90</sub>	C <sub>10</sub>	C <sub>90</sub>				
86	180	58	2.1	630 000	1 760 000	64 500	179 000		1 000	<b>29417 E</b>	

  

Dimensions (mm)						Dimensions de l'arbre (mm)		Dimensions Cotes de Montage (mm)				Masse (kg)
d <sub>1</sub>	D <sub>1</sub>	B <sub>1</sub> , B <sub>2</sub>	B <sub>3</sub>	C	A	d <sub>1a</sub>	d <sub>1c</sub>	d <sub>1d</sub>	D <sub>1a</sub>	D <sub>1c</sub>	r <sub>1a</sub>	
166.5	124	37	51.5	28	64	96	95	130	700	180	2	8.55



**Rodamiento axial de rodillos cónicos 29417-E-NSK**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	85
D - Diámetro exterior (mm)	180
C - Espesor (mm)	58
Marca	NSK
Tipo del rodamiento	Rodamiento axial de rodillos cónicos
Tipo de jaula	Acero
Rodamiento serie	29400
Unidad de venta	pieza

