



Rodamiento axial de rodillos cónicos 29420-E-NSK


29420-E-NSK



Version E



Version Standard



Dimensions (mm)				Capacité de Charge (N)				Viscosité (cSt) à 30°C	Résistance à l'usure
d	D	T	r	C ₉₀	C ₁₀₀	C ₉₀	C ₁₀₀		
90	210	67	5	840 000	2 400 000	86 900	245 900	1 600	29420 E

Dimensions (mm)						Dimensions des Lèvres (mm)		Dimensions Cotes de Montage (mm)					Massa (kg)	
d_1	D_1	B_1, B_2	B_2	C	A	d_{1a} max	d_{1c} max	$d_{1c}^{(1)}$ max	D_{1a} max	D_{1b} max	D_{1c} max	r_{1a}	r_{1b}	r_{1c}
185	344	43	58.5	30	62	111	111	150	175	214	2.5	10.3	10.3	10.3



Rodamiento axial de rodillos cónicos 29420-E-NSK

Caractéristique	Valeur
d - Diámetro interior (mm)	100
D - Diámetro exterior (mm)	210
C - Espesor (mm)	67
Marca	NSK
Tipo del rodamiento	Rodamiento axial de rodillos cónicos
Tipo de jaula	Acero
Rodamiento serie	29400
Unidad de venta	pieza

