

Rodamiento axial de rodillos cilíndricos 81103-T2-NTN

81103-T2-NTN

**LE BON
ROULEMENT**

**Type 811
Type 812**

WS

GS

Boundary dimensions

d	D	d ₁	D ₁	r	J _A	J _B	Z ₁	Z ₂	B	r _{max}
17	30	30	18	9	17	30	3.5	2.75	0.5	
					mm					
					811	812				

Basic load ratings

dynamic	static	dynamic	static
N	kgf	kgf	kgf
C ₁₀	C ₀	C ₁₀	C ₀
13 400	31 000	1 370	3 150

Limiting speeds

r/min	grease	oil
2 500	10 000	

Bearing numbers

bearing	first cylindrical roller and cage assembly	inner ring	outer ring
81103T2	KB1103T2	WS81103	GS81103

Reference dimensions

D ₁	D ₂
mm	mm
19.2	27.0

Abutment dimensions

r ₁	r ₂	r ₃
mm	mm	mm
27	20	0.3

Mass

kg	kg	kg
811	812	812
0.030	0.008	0.011



Rodamiento axial de rodillos cilíndricos 81103-T2-NTN

Caractéristique	Valeur
d - Diámetro interior (mm)	17
D - Diámetro exterior (mm)	30
C - Espesor (mm)	9
Marca	NTN
Tipo del rodamiento	Rodamiento axial de rodillos cilíndrico
Tipo de jaula	Poliamido
Rodamiento serie	81100
Unidad de venta	pieza

