

Rodamiento axial de rodillos cilíndricos 81109-T2-NTN

81109-T2-NTN

**LE BON
ROULEMENT**

**Type 811
Type 812**

WS

GS

Boundary dimensions

mm										
d	D	d ₁	D ₁	r	J ₁	J ₂	Z ₁	Z ₂	B	r _{max}
45	65	65	47	14	45	65	6	4	0.6	

Basic load ratings				Limiting speeds
dynamic	static	dynamic	static	
N		kgf		min
C ₁₀	C _{10s}	C ₉₀	C _{90s}	rpm
45 500	135 000	4 650	13 800	1 100

Limiting speeds	
min	max
rpm	oil
1 100	4 400

Bearing numbers

bearing	first cylindrical roller and cage assembly	inner ring	outer ring
81109T2	KB1109T2	WS81109	GS81109

Reference dimensions
mm

E ₁	E ₂
48.4	61.6

Abutment dimensions
mm

r ₁	r ₂	r _{1s}
61	49	0.6

Mass
kg

811	812	800
0.150	0.040	0.055



Rodamiento axial de rodillos cilíndricos 81109-T2-NTN

Caractéristique	Valeur
d - Diámetro interior (mm)	45
D - Diámetro exterior (mm)	65
C - Espesor (mm)	14
Marca	NTN
Tipo del rodamiento	Rodamiento axial de rodillos cilíndrico
Tipo de jaula	Poliamido
Rodamiento serie	81100
Unidad de venta	pieza

