

Rodamiento axial de rodillos cilíndricos 81206-T2-NTN

81206-T2-NTN

**LE BON
ROULEMENT**

**Type 811
Type 812**

WS

GS

Boundary dimensions

mm										Basic load ratings				Limiting speeds		
d	D	d_1	D_1	r	J_1	J_2	Z_1	Z_2	B	r_{max}	dynamic N	static kN	dynamic kN	static kN	r/min grease	r/min oil
30	52	52	32	16	30	52	7.5	4.25	0.6		53 000	129 000	5 450	13 100	1 500	6 000

Bearing numbers

Reference dimensions

Abutment dimensions

Mass

bearing	first cylindrical roller and cage assembly	inner ring	outer ring	D_1	D_2	r_1	r_2	r_{1s}	r_{2s}	811 812	812 812	812 812
81206T2	KR1206T2	WS81206	GS81206	32.8	49.0	45	33	0.6		0.140	0.050	0.045



Rodamiento axial de rodillos cilíndricos 81206-T2-NTN

Caractéristique	Valeur
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	52
C - Espesor (mm)	16
Marca	NTN
Tipo del rodamiento	Rodamiento axial de rodillos cilíndrico
Tipo de jaula	Poliamido
Rodamiento serie	81200
Unidad de venta	pieza

