

Rodamiento axial de rodillos cilíndricos 81207-T2-NTN

81207-T2-NTN

**LE BON
ROULEMENT**

**Type 811
Type 812**

WS

GS

Boundary dimensions

mm										
d	D	d ₁	D ₁	r	J ₁	J ₂	Z ₁	Z ₂	B	r _{max}
35	62	62	37	18	35	62	7.5	5.25	1	

dynamic

N
C ₁₀
54 500

static

N
C ₀₁₀
139 000

dynamic

kgf
C ₁₀
5 550

static

kgf
C ₀₁₀
14 200

Limiting speeds

min	max
grease	oil
1 200	4 900

Bearing numbers

bearing	first cylindrical roller and cage assembly	inner ring	outer ring
81207T2	K81207T2	WS81207	GS81207

Reference dimensions

mm	D ₁	D ₂
	30.8	58.0

Abutment dimensions

mm	r ₁	r ₂	r ₃
	56	41	1

Mass

kg	811	812	812
	0.235	0.065	0.085



Rodamiento axial de rodillos cilíndricos 81207-T2-NTN

Caractéristique	Valeur
d - Diámetro interior (mm)	35
D - Diámetro exterior (mm)	62
C - Espesor (mm)	18
Marca	NTN
Tipo del rodamiento	Rodamiento axial de rodillos cilíndrico
Tipo de jaula	Poliamido
Rodamiento serie	81200
Unidad de venta	pieza

