

Rodamiento axial de rodillos cilíndricos 89306-NTN

89306-NTN

**LE BON
ROULEMENT**

Type 893

Type K893

WS

GS

Boundary dimensions

d	D	d_1	D_1	T	d_2	D_2	d_3	D_3	B	r_{max}
mm										
30	60	60	32	18	30	60	5.5	6.25	1	

dynamic

C_{10}
54 000

static

C_{010}
166 000

dynamic

C_{10}
5 500

static

C_{010}
16 900

Limiting speeds

min	max
1 300	5 000

Bearing numbers

bearing	first cylindrical roller and cage assembly	inner ring	outer ring
89306	K89306	WS89306	GS89306

Reference dimensions

D_1	D_2
34.0	56.4

Abutment dimensions

d_1	d_2	r_{1a}
56	34	1

Mass

m_{11}	m_{12}	m_{13}
0.250	0.046	0.100



Rodamiento axial de rodillos cilíndricos 89306-NTN

Caractéristique	Valeur
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	60
C - Espesor (mm)	18
Marca	NTN
Tipo del rodamiento	Rodamiento axial de rodillos cilíndrico
Tipo de jaula	Acero
Rodamiento serie	89300
Unidad de venta	pieza

