

Rodamiento axial de rodillos cilíndricos 89309-NTN

89309-NTN

**LE BON
ROULEMENT**

Type BR3

Type K893

WS

GS

Boundary dimensions

mm
 d D d_1 D_1 T d_2 D_2 d_3 D_3 B r_{max}

45 85 85 47 24 45 85 7.5 8.25 1

Basic load ratings

dynamic static dynamic static
N kN kN kN
 C_{10} C_{010} C_{10} C_{010}

102 000 345 000 10 400 35 000

Limiting speeds

r/min
grease oil
 n_{gr} n_{oil}

900 3 600

Bearing numbers

bearing first cylindrical roller and cage assembly inner ring outer ring

89309 K89309 WS89309 GS89309

Reference dimensions

mm
 d_1 d_2

50.9 81.3

Abutment dimensions

mm
 d_1 d_2 r_{max} r_{min}

81 51 1

Mass

kg
811 812 813
 m_{811} m_{812} m_{813}

0.670 0.140 0.270



Rodamiento axial de rodillos cilíndricos 89309-NTN

Caractéristique	Valeur
d - Diámetro interior (mm)	45
D - Diámetro exterior (mm)	85
C - Espesor (mm)	24
Marca	NTN
Tipo del rodamiento	Rodamiento axial de rodillos cilíndrico
Tipo de jaula	Acero
Rodamiento serie	89300
Unidad de venta	pieza

