

Rodamiento axial de rodillos cilíndricos AZK10243,5-IKO

AZK10243,5-IKO

**LE BON
ROULEMENT**

Identification number

Shaft dia. mm	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
10	AZ 10249	24.6	AZK 10243.5	8.6	WS 1024	GS 1024	8

Boundary dimensions
mm

Standard mounting
dimensions mm

Basic dynamic
load rating
 C

Basic static
load rating
 C_0

Allowable
rotational
speed

d	D	T	d_e	D_e	D_w	B	$r_{3, \min}$	C_1	C_2	d_B Min.	D_B Max.	N	N	rpm
10	24	9	10.04	23.6	3.5	2.75	0.3	13	21	21	13	8 990	19 100	18 000



Rodamiento axial de rodillos cilíndricos AZK10243,5-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	10
D - Diámetro exterior (mm)	24
C - Espesor (mm)	3,5
Marca	IKO
Tipo del rodamiento	Rodamiento axial de rodillos cilíndrico
Rodamiento serie	AZK
Unidad de venta	pieza

