

# Arandela para rodamiento axial de rodillos GS110160-IKO

## GS110160-IKO

 **LE BON  
ROULEMENT**



| Shaft dia.<br>mm | Identification number |               |                       |               |                  |                  |               |
|------------------|-----------------------|---------------|-----------------------|---------------|------------------|------------------|---------------|
|                  | Thrust roller bearing | Mass (Ref.) g | Thrust roller bearing | Mass (Ref.) g | Inner ring       | Outer ring       | Mass (Ref.) g |
| 110              | <b>AZ 11016040</b>    | 3 220         | <b>AZK 11016017</b>   | 1 320         | <b>WS 110160</b> | <b>GS 110160</b> | 950           |

  

| Boundary dimensions mm |     |    |                |                |                 |      |                    |                |                | Sintered bearing dimensions mm |                        | Basic dynamic load rating | Basic static load rating | Allowable rotational speed |
|------------------------|-----|----|----------------|----------------|-----------------|------|--------------------|----------------|----------------|--------------------------------|------------------------|---------------------------|--------------------------|----------------------------|
| d                      | D   | T  | d <sub>c</sub> | D <sub>c</sub> | D <sub>se</sub> | B    | r <sub>5,ref</sub> | C <sub>1</sub> | C <sub>2</sub> | d <sub>5</sub><br>Min.         | D <sub>5</sub><br>Max. | C<br>N                    | C <sub>0</sub><br>N      | rpm                        |
| 110                    | 160 | 40 | 110,1          | 159,5          | 17              | 11,5 | 1,1                | 120            | 154            | 153                            | 121                    | 282 000                   | 1 030 000                | 2 000                      |



**Arandela para rodamiento axial de rodillos GS110160-IKO**

| Caractéristique            | Valeur                                                      |
|----------------------------|-------------------------------------------------------------|
| d - Diámetro interior (mm) | 110                                                         |
| D - Diámetro exterior (mm) | 160                                                         |
| C - Espesor (mm)           | 11,5                                                        |
| Marca                      | IKO                                                         |
| Tipo del rodamiento        | Arandela para rodamiento extrema presión y baja temperatura |
| Unidad de venta            | pieza                                                       |

