

# Arandela para rodamiento axial de rodillos GS1730-IKO

## GS1730-IKO

**LE BON  
ROULEMENT**

Identification number

| Shaft dia.<br>mm | Thrust roller bearing | Mass (Ref.)<br>g | Thrust roller bearing | Mass (Ref.)<br>g | Inner ring | Outer ring | Mass (Ref.)<br>g |
|------------------|-----------------------|------------------|-----------------------|------------------|------------|------------|------------------|
| 17               | AZ 17309              | 30.5             | AZK 17303.5           | 10.1             | WS 1730    | GS 1730    | 10.2             |

| Boundary dimensions<br>mm |    |   |                |                |                 |      |                    |                |                | Standard bearing<br>dimensions mm | Basic dynamic<br>load rating<br>C | Basic static<br>load rating<br>C <sub>0</sub> | Allowable<br>rotational<br>speed<br>rpm |        |
|---------------------------|----|---|----------------|----------------|-----------------|------|--------------------|----------------|----------------|-----------------------------------|-----------------------------------|-----------------------------------------------|-----------------------------------------|--------|
| d                         | D  | T | d <sub>e</sub> | D <sub>e</sub> | D <sub>90</sub> | B    | r <sub>3 min</sub> | C <sub>1</sub> | C <sub>2</sub> | d <sub>2</sub><br>Min.            | D <sub>2</sub><br>Max.            | N                                             | N                                       |        |
| 17                        | 30 | 9 | 17.04          | 29.6           | 3.5             | 2.75 | 0.3                | 19             | 27             | 27                                | 20                                | 11 400                                        | 28 600                                  | 13 000 |



**Arandela para rodamiento axial de rodillos GS1730-IKO**

| Caractéristique            | Valeur                                                      |
|----------------------------|-------------------------------------------------------------|
| d - Diámetro interior (mm) | 17                                                          |
| D - Diámetro exterior (mm) | 30                                                          |
| C - Espesor (mm)           | 2,75                                                        |
| Marca                      | IKO                                                         |
| Tipo del rodamiento        | Arandela para rodamiento extrema presión y baja temperatura |
| Unidad de venta            | pieza                                                       |

