

# Arandela para rodamiento axial de rodillos GS4565-IKO

## GS4565-IKO

 **LE BON  
ROULEMENT**



| Shaft dia.<br>mm | Identification number |               |                       |               |            |            |               |
|------------------|-----------------------|---------------|-----------------------|---------------|------------|------------|---------------|
|                  | Thrust roller bearing | Mass (Ref.) g | Thrust roller bearing | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g |
| 45               | AZ 456514             | 169           | AZK 45656             | 62            | WS 4565    | GS 4565    | 53.5          |

  

| Boundary dimensions mm |    |    |                |                |                 |   |                     |                |                | Sintered bearing dimensions mm |                         | Basic dynamic load rating | Basic static load rating | Allowable rotational speed |
|------------------------|----|----|----------------|----------------|-----------------|---|---------------------|----------------|----------------|--------------------------------|-------------------------|---------------------------|--------------------------|----------------------------|
| d                      | D  | T  | d <sub>e</sub> | D <sub>e</sub> | D <sub>se</sub> | B | r <sub>3, min</sub> | C <sub>i</sub> | C <sub>e</sub> | d <sub>sa</sub><br>Min.        | D <sub>sa</sub><br>Max. | C                         | C <sub>0</sub>           | rpm                        |
| 45                     | 65 | 14 | 45.05          | 64.5           | 6               | 4 | 0.6                 | 49             | 62             | 62                             | 49                      | 40 800                    | 133 000                  | 5 500                      |



**Arandela para rodamiento axial de rodillos GS4565-IKO**

| Caractéristique            | Valeur                                                      |
|----------------------------|-------------------------------------------------------------|
| d - Diámetro interior (mm) | 45                                                          |
| D - Diámetro exterior (mm) | 65                                                          |
| C - Espesor (mm)           | 4                                                           |
| Marca                      | IKO                                                         |
| Tipo del rodamiento        | Arandela para rodamiento extrema presión y baja temperatura |
| Unidad de venta            | pieza                                                       |

