

# Arandela para rodamiento axial de rodillos GS4573-IKO

## GS4573-IKO



| Shaft dia.<br>mm | Identification number |               |                       |               |            |            |               |
|------------------|-----------------------|---------------|-----------------------|---------------|------------|------------|---------------|
|                  | Thrust roller bearing | Mass (Ref.) g | Thrust roller bearing | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g |
| 45               | AZ 457320             | 360           | AZK 45739             | 144           | WS 4573    | GS 4573    | 106           |

  

| Boundary dimensions mm |    |    |                |                |                |     |                     |                |                | Sealed bearing dimension mm | Basic dynamic load rating C | Basic static load rating C <sub>0</sub> | Allowable rotational speed |
|------------------------|----|----|----------------|----------------|----------------|-----|---------------------|----------------|----------------|-----------------------------|-----------------------------|-----------------------------------------|----------------------------|
| d                      | D  | T  | d <sub>e</sub> | D <sub>e</sub> | D <sub>W</sub> | B   | r <sub>3, min</sub> | C <sub>1</sub> | C <sub>2</sub> | d <sub>2</sub> Min. Max.    | N                           | N                                       | rpm                        |
| 45                     | 73 | 20 | 45.05          | 72.5           | 9              | 5.5 | 1                   | 50             | 69             | 69 51                       | 75 700                      | 227 000                                 | 5 000                      |



**Arandela para rodamiento axial de rodillos GS4573-IKO**

| Caractéristique            | Valeur                                                      |
|----------------------------|-------------------------------------------------------------|
| d - Diámetro interior (mm) | 45                                                          |
| D - Diámetro exterior (mm) | 73                                                          |
| C - Espesor (mm)           | 5,5                                                         |
| Marca                      | IKO                                                         |
| Tipo del rodamiento        | Arandela para rodamiento extrema presión y baja temperatura |
| Unidad de venta            | pieza                                                       |

