


# Arandela para rodamiento axial de rodillos GS81207-NTN

## GS81207-NTN

 **LE BON  
ROULEMENT**



| Boundary dimensions |    |     |    |     |                |                |                |                |                | Basic load ratings |             |                |               | Limiting speeds |       |
|---------------------|----|-----|----|-----|----------------|----------------|----------------|----------------|----------------|--------------------|-------------|----------------|---------------|-----------------|-------|
| d                   | D  | r   | B  | r   | D <sub>1</sub> | B <sub>1</sub> | r <sub>1</sub> | B <sub>2</sub> | r <sub>2</sub> | dynamic<br>N       | static<br>N | dynamic<br>kgf | static<br>kgf | min<br>grease   | oil   |
| 35                  | 62 | 0.2 | 37 | 0.1 | 62             | 35             | 0.1            | 62             | 0.1            | 54 500             | 139 000     | 5 550          | 14 200        | 1 200           | 4 900 |

| Bearing numbers |                                            |            |            | Reference dimensions |                | Abutment dimensions |                |                | Mass  |       |       |
|-----------------|--------------------------------------------|------------|------------|----------------------|----------------|---------------------|----------------|----------------|-------|-------|-------|
| bearing         | first cylindrical roller and cage assembly | inner ring | outer ring | D <sub>1</sub>       | D <sub>2</sub> | r <sub>1</sub>      | r <sub>2</sub> | r <sub>3</sub> | 811   | 812   | 813   |
| 81207T2         | K81207T2                                   | WS81207    | GS81207    | 30.8                 | 56.0           | 56                  | 41             | 1              | 0.235 | 0.065 | 0.085 |



**Arandela para rodamiento axial de rodillos GS81207-NTN**

| Caractéristique            | Valeur                                                      |
|----------------------------|-------------------------------------------------------------|
| d - Diámetro interior (mm) | 37                                                          |
| D - Diámetro exterior (mm) | 62                                                          |
| C - Espesor (mm)           | 5,25                                                        |
| Marca                      | NTN                                                         |
| Tipo del rodamiento        | Arandela para rodamiento extrema presión y baja temperatura |
| Unidad de venta            | pieza                                                       |

