

## Rodamiento axial de rodillos cilíndricos K81120-T2-NTN

K81120-T2-NTN



# LE BON ROULEMENT



| Boundary dimensions |     |     |     |     |       |       |       |       |       | Basic load ratings |           |          |           | Limiting speeds |       |
|---------------------|-----|-----|-----|-----|-------|-------|-------|-------|-------|--------------------|-----------|----------|-----------|-----------------|-------|
| mm                  |     |     |     |     |       |       |       |       |       | N                  |           |          |           | r/min           |       |
| $d$                 | $D$ | $B$ | $E$ | $r$ | $d_1$ | $D_1$ | $D_2$ | $B_1$ | $B_2$ | dynamic            | static    | dynamic  | static    | grease          | oil   |
|                     |     |     |     |     | E11   | E12   | E13   | E14   | E15   | $C_{10}$           | $C_{100}$ | $C_{10}$ | $C_{100}$ |                 |       |
| 109                 | 135 | 135 | 102 | 25  | 100   | 135   | 11    | 7     | 1     | 158 000            | 555 000   | 16 100   | 67 000    | 500             | 2 000 |

  

| Bearing numbers |                                            |            |            | Reference dimensions<br>mm |       | Adjustment dimensions<br>mm |              |              | Mass<br>kg        |            |            |
|-----------------|--------------------------------------------|------------|------------|----------------------------|-------|-----------------------------|--------------|--------------|-------------------|------------|------------|
| bearing         | fixed cylindrical roller and cage assembly | inner ring | outer ring | $E_1$                      | $E_2$ | $d_1$<br>min                | $D_1$<br>max | $r_1$<br>max | E11<br>E12<br>E13 | E14<br>E15 | E16<br>E17 |
| 81120T2         | K81120T2                                   | WS81120    | GS81120    | 106.1                      | 128.7 | 128                         | 106          | 1            | 1.000             | 0.300      | 0.350      |



**Rodamiento axial de rodillos cilíndricos K81120-T2-NTN**

| Caractéristique            | Valeur                                  |
|----------------------------|-----------------------------------------|
| d - Diámetro interior (mm) | 100                                     |
| D - Diámetro exterior (mm) | 135                                     |
| C - Espesor (mm)           | 11                                      |
| Marca                      | NTN                                     |
| Tipo del rodamiento        | Rodamiento axial de rodillos cilíndrico |
| Rodamiento serie           | K81100                                  |
| Unidad de venta            | pieza                                   |

