

Arandela para rodamiento axial de rodillos LS1528-SKF

LS1528-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit		Minimum load factor		Speed ratings		Mass	Designation	
d	D	H	E ₁	E ₂	C	C ₀	P ₀	A	Reference speed	Limiting speed	kg	
mm					klN	klN	–	r/min				
15	28	9	16	27	11.2	27	2.45	0.000 058	4 500	8 500	0.024	63322 TN

Dimensions		Abutment and fillet dimensions				Designation of components			Housing washer	Universal washer	
d	d ₁	D ₁	B	E ₁	r _{1,2}	d ₁	D ₁	r _{1,2}	Cylindrical roller bearing fit assembly	Short washer	
mm					mm	mm	mm	mm			
15	28	16	2,75	3,3	0,3	27	16	0,3	K 621502 TN	WS 621502	GG 621502 LS 1528



Arandela para rodamiento axial de rodillos LS1528-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	15
D - Diámetro exterior (mm)	28
C - Espesor (mm)	2,75
Marca	SKF
Tipo del rodamiento	Arandela para rodamiento extrema presión y baja temperatura
Unidad de venta	pieza

