

Arandela para rodamiento axial de rodillos LS2035-SKF

LS2035-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit		Minimum load factor		Speed ratings		Mass	Designation	
d	D	H	E ₁	E ₂	C	C ₀	P ₀	A	Reference speed	Limiting speed	kg	
mm					ISO	ISO	–	r/min				–
20	35	18	23	24	18.6	48	4.65	0.00185	1800	7500	0.027	62184 TN

Dimensions		Abutment and fillet dimensions				Designation of components			Housing washer	Universal washer		
d	d ₁	D ₁	B	E ₁	r _{1,2}	r ₁	r ₂	r ₃	Cylindrical roller bearing fit assembly	Short washer		Universal washer
mm					mm	mm	mm	mm	–	–		
20	38	24	2,75	4,5	0,3	0,3	0,3	0,3	K 62104 TN	WS 62104	GG 62184	LS 2035



Arandela para rodamiento axial de rodillos LS2035-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	20
D - Diámetro exterior (mm)	35
C - Espesor (mm)	2,75
Marca	SKF
Tipo del rodamiento	Arandela para rodamiento extrema presión y baja temperatura
Unidad de venta	pieza

