


Arandela para rodamiento axial de rodillos LS4060-SKF

LS4060-SKF

LE BON ROULEMENT



| Principal dimensions | | Basic load ratings | | Fatigue load limit | Minimum load factor | Speed ratings | Mass | Designation | | | | |
|----------------------|----|--------------------|-------|--------------------|---------------------|-----------------|----------------|-------------|------|------|------|----------|
| d | D | H | C_0 | C_0 | F_0 | Reference speed | Limiting speed | | | | | |
| mm | | | | | | r/min | kg | | | | | |
| 40 | 60 | 13 | 42 | 58 | 43 | 137 | 13,7 | 0,0885 | 2400 | 1000 | 0,11 | 83188 TN |

| Dimensions | | Abutment and fillet dimensions | | | | Designation of components | | | Housing washer | Universal washer | | |
|------------|-------|--------------------------------|------|-------|-----------|---------------------------|-------|-------|---|------------------|----------|---------|
| d | d_1 | D_1 | B | D_2 | $r_{1,2}$ | r_1 | r_2 | r_3 | Cylindrical roller bearing fit assembly | Short washer | | |
| mm | | | | | mm | mm | mm | mm | | | | |
| 40 | 60 | 42 | 13,5 | 4 | 0,6 | 0,8 | 0,2 | 0,6 | K 82108 TN | WS 81108 | GG 82188 | LS 6360 |



Arandela para rodamiento axial de rodillos LS4060-SKF

| Caractéristique | Valeur |
|----------------------------|---|
| d - Diámetro interior (mm) | 40 |
| D - Diámetro exterior (mm) | 60 |
| C - Espesor (mm) | 3,5 |
| Marca | SKF |
| Tipo del rodamiento | Arandela para rodamiento extrema presión y baja temperatura |
| Unidad de venta | pieza |

