

Arandela para rodamiento axial de rodillos WS81112-SKF

WS81112-SKF

LE BON ROULEMENT



Principal dimensions		Basic load ratings		Fatigue load limit	Minimum load factor	Speed ratings		Mass	Designation			
d	D	H	E ₁	E ₂	C _d	C ₀	F ₀	A	Reference speed	Limiting speed	kg	
mm					ISO	ISO	–	r/min				–
40	85	17	42	32	80	330	36.5	0.0072	1000	1400	0.27	81112 TN

Dimensions		Abutment and fillet dimensions				Designation of components			Housing washer	Universal washer		
d	d ₁	D ₁	B	E ₁	r _{1,2}	d ₁	D ₁	r _{1,2}	Cylindrical roller bearing fit assembly	Short washer		
mm					mm	mm	mm	mm	–	–		
40	85	62	4.75	7.0	1	82	62	1	K 82012 TN	WS 81112	GG 82012	LS 4005



Arandela para rodamiento axial de rodillos WS81112-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	60
D - Diámetro exterior (mm)	85
C - Espesor (mm)	4,75
Marca	SKF
Tipo del rodamiento	Arandela para rodamiento extrema presión y baja temperatura
Unidad de venta	pieza

